

## SUPPRESSOR FOR CONTACTORS


Diode, 24....240 VDC, 50 W


24...240 V DC Diode For other configurations and voltages, please inquire.

## Link to Product

Illustration







Product may differ from Image



| Commercial data |          |  |
|-----------------|----------|--|
| ECLASS-6.0      | 27371013 |  |
| ECLASS-6.1      | 27371013 |  |
| ECLASS-7.0      | 27371013 |  |
| ECLASS-8.0      | 27371013 |  |
| ECLASS-9.0      | 27371013 |  |
| ECLASS-10.1     | 27371013 |  |

The information in this Product-PDF has been compiled with the utmost care. Liability for the correctness completeness and topicality of the information is restricted to gross negligence. Version: 2024-05-10

Murrelektronik Canada | 2840 Argentia Rd Unit #9 | L5N 8G4 Mississauga, ON | Fon +1 905-362-2211 | Fax +1 905-362-2101 | shop@murr.ca | shop.murr.ca



| ECLASS-11.1                              | 27371013      |
|--|---------------|
| ECLASS-12.0                              | 27371013      |
| ETIM-5.0                                 | EC002498      |
| customs tariff number                    | 85363010      |
| GTIN                                     | 4048879018647 |
| Packaging unit                           | 1             |
| Compatibility   Compatible with          |               |
| Appropriate contactors                   | universal     |
| Electrical data                          |               |
| Holding power max.                       | 50 W          |
| Electrical data   Input                  |               |
| Input voltage DC min.                    | 24 V          |
| Input voltage DC max.                    | 240 V         |
| Mechanical data   Mounting data          |               |
| Height                                   | 20 mm         |
| Width                                    | 43 mm         |
| Depth                                    | 12 mm         |
| Environmental characteristics   Climatic |               |
| Operating temperature min.               | -20 °C        |
| Operating temperature max.               | 70 °C         |

The information in this Product-PDF has been compiled with the utmost care. Liability for the correctness completeness and topicality of the information is restricted to gross negligence. Version: 2024-05-10

Murrelektronik Canada | 2840 Argentia Rd Unit #9 | L5N 8G4 Mississauga, ON | Fon +1 905-362-2211 | Fax +1 905-362-2101 | shop@murr.ca | shop.murr.ca