

## MIRO TR 24VDC SK 2A 5P OPTO-COUPLER MODULE


IN: 53 VDC - OUT: 48 VDC / 2 A


Transistor 2 A 24 V DC Inrush current limiting with solder terminal Screw terminals

## **Link to Product**

## Illustration







Product may differ from Image









Commercial data		
ECLASS-6.0	27371604	
ECLASS-6.1	27371604	
ECLASS-7.0	27371604	
ECLASS-8.0	27371604	
ECLASS-9.0	27371604	

The information in this Product-PDF has been compiled with the utmost care.
Liability for the correctness completeness and topicality of the information is restricted to gross negligence. Version: 2024-05-20



stay connected

EOLASS 10.1	27271504
ECLASS-10.1 ECLASS-11.1	27371604
ECLASS-11.1 ECLASS-12.0	27371604
ETIM-5.0	27371604 EC001504
customs tariff number	85414900
GTIN	4048879026840
Packaging unit	1
	1
Electrical data   Input	
Input voltage OFF DC min.	0 V
Input voltage OFF DC max.	5 V
Input voltage DC min.	10 V
Input voltage DC max.	53 V
Current input DC	7 mA
Electrical data   Output	
Overload resistant	yes
Switch off delay max.	10 ms
Switch on delay max.	5 ms
Quiescent current OFF max.	0,1 mA
Switching frequency max.	10 Hz
Voltage switching DC min.	5 V
Switching voltage DC max.	48 V
Switching current min.	1 mA
Switching current max.	2 A
Voltage drop DC max.	0,35 V
Diagnostics	
Status indication LED	yellow
Device protection   Electrical	
Rated surge voltage	2,5 kV
Device protection   Media	
Flame resistance	flame retardant
Mechanical data   Material data	
Color housing	black
Material housing	Plastic
Mechanical data   Mounting data	
	goodhaant
Mounting method	geschnappt
Suitable for mounting type Height	mounting rail, (EN 60715)  91 mm
Width	6,2 mm
Depth	6,2 mm 71 mm
Environmental characteristics   Climatic	7 1 11011
· ·	
Operating temperature min.	-20 °C
Operating temperature max.	60 °C
Connection type 5	
Connection	Screw terminals SK
Family construction form	terminal
Gender	female
Color contact carrier	green
No. of poles	1
PIN 1	13 +
Connection	Screw terminals SK
Family construction form	terminal

The information in this Product-PDF has been compiled with the utmost care. Liability for the correctness completeness and topicality of the information is restricted to gross negligence. Version: 2024-05-20



stay connected

Gender	female
Color contact carrier	green
No. of poles	1
PIN 1	NC
Connection	Screw terminals SK
Family construction form	terminal
Gender	female
Color contact carrier	green
No. of poles	1
PIN 1	14
Connection	Screw terminals SK
Family construction form	terminal
Gender	female
Color contact carrier	green
No. of poles	1
PIN 1	A 1
Connection	Screw terminals SK
Family construction form	terminal
Gender	female
Color contact carrier	green
No. of poles	1
PIN 1	A 2