

MIRO TR 24VDC 24VDC 10A SK OPTO-COUPLER MODULE


IN: 53 VDC - OUT: 48 VDC / 10 A


Transistor 10 A 24 V DC Screw terminals

Link to Product

Illustration







Product may differ from Image









Commercial data		
ECLASS-6.0	27371604	
ECLASS-6.1	27371604	
ECLASS-7.0	27371604	
ECLASS-8.0	27371604	
ECLASS-9.0	27371604	
ECLASS-10.1	27371604	



stay connected

FOLACO 11 1	27371604
ECLASS-11.1	
ECLASS-12.0	27371604
ETIM-5.0	EC001504
customs tariff number	85414900
GTIN	4048879026802
Packaging unit	1
Electrical data Input	
Input voltage OFF DC min.	0 V
Input voltage OFF DC max.	5 V
Input voltage DC min.	10 V
Input voltage DC max.	53 V
Current input DC	10 mA
Electrical data Output	
Switch-off delay resistive load max.	5000 μs
On-delay resistive load max.	2000 μs
Quiescent current OFF max.	0,025 mA
Switching frequency inductive max.	0,1 Hz
Switching frequency ohmic max.	1 Hz
Voltage switching DC min.	5 V
Switching voltage DC max.	48 V
Switching current min.	1 mA
Switching current max.	10 A
Voltage drop DC max.	0,12 V
Diagnostics	
Status indication LED	yellow
Device protection Electrical	
Rated insulation voltage	2750 V
Device protection Media	
Flame resistance	flame retardant
Mechanical data Material data	
Color housing	black
Material housing	Plastic
Mechanical data Mounting data	
	accebnant
Mounting method	geschnappt
Suitable for mounting type Height	mounting rail, (EN 60715) 78 mm
Width	6,2 mm
Depth	70 mm
	70 IIIII
Environmental characteristics Climatic	
Operating temperature min.	-20 °C
Operating temperature max.	60 °C
Connection type 4	
Connection	Screw terminals SK
Family construction form	terminal
Gender	female
Color contact carrier	green
No. of poles	1
PIN 1	13 +
Connection	Screw terminals SK
Family construction form	terminal
Gender	female

The information in this Product-PDF has been compiled with the utmost care. Liability for the correctness completeness and topicality of the information is restricted to gross negligence. Version: 2024-05-10



Color contact carrier	green	
No. of poles	1	
PIN 1	14	
Connection	Screw terminals SK	
Family construction form	terminal	
Gender	female	
Color contact carrier	green	
No. of poles	1	
PIN 1	A 1	
Connection	Screw terminals SK	
Family construction form	terminal	
Gender	female	
Color contact carrier	green	
No. of poles	1	
PIN 1	A 2	