


Xelity 6TX Unmanaged Switch 6 Port 100Mbit

6 port unmanaged switch Connection cables are in the online shop under "Connection Technology".

Link to Product

Illustration



Product may differ from Image



Commercial data	
ECLASS-6.0	19170106
ECLASS-6.1	19170106
ECLASS-7.0	19170106
ECLASS-8.0	19170106
ECLASS-9.0	19170402
ECLASS-10.1	19170402
ECLASS-11.1	19170402
ECLASS-12.0	19170402
ETIM-5.0	EC000734
customs tariff number	85176200
GTIN	4048879798396
Packaging unit	1
Electrical data Supply	
Operating voltage DC min.	9,5 V
Operating voltage DC max.	31,5 V
Industrial communication	
Data transmission rate max.	100 MBit/s
Industrial communication Ethernet for	unctionality
Auto-crossover	yes
Auto-negotiation	yes
duplex	Full duplex
Switch type	unmanaged
VLAN unmanaged (IEEE 802.1Q)	yes

The information in this Product-PDF has been compiled with the utmost care. Liability for the correctness completeness and topicality of the information is restricted to gross negligence. Version: 2024-05-05

Murrelektronik Canada | 2840 Argentia Rd Unit #9 | L5N 8G4 Mississauga, ON | Fon +1 905-362-2211 | Fax +1 905-362-2101 | shop@murr.ca | shop.murr.ca



Diagnostics	
Alarm contact	no
Diagnostic	No voltage
LED display	Ethernet connection/data traffic
Device protection Electrical	
Degree of protection (EN IEC 60529)	IP20
Invers-polarity protection	yes
Over voltage protection	yes
Mechanical data Material data	
Color housing	black
Material housing	Plastic
Mechanical data Mounting data	
Mounting method	geschnappt
Suitable for mounting type	Mounting rail TH35, (EN 60715)
Height	140 mm
Width	30 mm
Depth	85,1 mm
Environmental characteristics Climatic	
Operating temperature min.	-25 °C
Operating temperature max.	0° 00
Storage temperature min.	-40 °C
Storage temperature max.	85 °C
Connection type 2	
Connection type 1	6
Family construction form	RJ45
Gender	female
Color contact carrier	black
No. of poles	8
PIN 1	TD +
PIN 2	TD + TD -
PIN 2 PIN 3	TD + TD - RD +
PIN 2 PIN 3 PIN 4	TD + TD - RD + n.c.
PIN 2 PIN 3 PIN 4 PIN 5	TD + TD - RD + n.c. n.c.
PIN 2 PIN 3 PIN 4 PIN 5 PIN 6	TD + TD - RD + n.c. n.c. RD -
PIN 2 PIN 3 PIN 4 PIN 5 PIN 6 PIN 7	TD + TD - RD + n.c. n.c. RD - n.c.
PIN 2 PIN 3 PIN 4 PIN 5 PIN 6	TD + TD - RD + n.c. n.c. RD -
PIN 2 PIN 3 PIN 4 PIN 5 PIN 6 PIN 7 PIN 8	TD + TD - RD + n.c. n.c. RD - n.c. n.c. n.c. n.c. n.c. n.c. n.c.
PIN 2 PIN 3 PIN 4 PIN 5 PIN 6 PIN 7 PIN 8 Connection	TD + TD - RD + n.c. n.c. RD - n.c. Spring clamp terminals FK
PIN 2 PIN 3 PIN 4 PIN 5 PIN 6 PIN 7 PIN 8 Connection Family construction form	TD + TD - RD + n.c. n.c. RD - n.c. n.c. Spring clamp terminals FK terminal
PIN 2 PIN 3 PIN 4 PIN 5 PIN 6 PIN 7 PIN 8 Connection Family construction form Gender Color contact carrier No. of poles	TD + TD - RD + n.c. n.c. RD - n.c. n.c. Spring clamp terminals FK terminal female green 4
PIN 2 PIN 3 PIN 4 PIN 5 PIN 6 PIN 7 PIN 8 Connection Family construction form Gender Color contact carrier No. of poles PIN 1	TD + TD - RD + n.c. n.c. RD - n.c. n.c. Spring clamp terminals FK terminal female green 4 24 V DC (UB 1)
PIN 2 PIN 3 PIN 4 PIN 5 PIN 6 PIN 7 PIN 8 Connection Family construction form Gender Color contact carrier No. of poles PIN 1 PIN 2	TD + TD - RD + n.c. n.c. RD - n.c. n.c. n.c. Spring clamp terminals FK terminal female green 4 24 V DC (UB 1) 0 V
PIN 2 PIN 3 PIN 4 PIN 5 PIN 6 PIN 7 PIN 8 Connection Family construction form Gender Color contact carrier No. of poles PIN 1	TD + TD - RD + n.c. n.c. RD - n.c. n.c. Spring clamp terminals FK terminal female green 4 24 V DC (UB 1)

The information in this Product-PDF has been compiled with the utmost care. Liability for the correctness completeness and topicality of the information is restricted to gross negligence. Version: 2024-05-05

Murrelektronik Canada | 2840 Argentia Rd Unit #9 | L5N 8G4 Mississauga, ON | Fon +1 905-362-2211 | Fax +1 905-362-2101 | shop@murr.ca | shop.murr.ca