

INTERFACE TERMINAL RELAY


IN: 24 VDC - OUT: 24VDC / 0.2 A / 20 kHz


Transistor 0.2 A 24 V DC Control current 2.8 mA (24 V DC) Spring clamp terminals

Link to Product

Illustration







Product may differ from Image





Commercial data		
ECLASS-6.0	27371604	
ECLASS-6.1	27371604	
ECLASS-7.0	27371604	
ECLASS-8.0	27371604	
ECLASS-9.0	27371604	
ECLASS-10.1	27371604	

The information in this Product-PDF has been compiled with the utmost care.
Liability for the correctness completeness and topicality of the information is restricted to gross negligence. Version: 2024-05-20



stay connected

ECLASS-11.1	27371604
ECLASS-11.1	27371604
ETIM-5.0	EC001504
customs tariff number	85414900
GTIN	4048879024549
Packaging unit	1
Electrical data Input	
	0 V
Input voltage OFF DC min.	5 V
Input voltage OFF DC max. Input voltage DC	24 V
Input voltage DC min.	16 V
Input voltage DC max.	30 V
Input current DC max.	16 mA
Electrical data Output	
Switch off delay max.	20 µs
Quiescent current OFF max.	0,1 mA
Switching frequency max. Voltage switching DC min.	20000 Hz 5 V
Switching voltage DC max.	48 V
Switching current min.	0,1 mA
Switching current max.	0,2 A
Voltage drop DC max.	1,2 V
Diagnostics	-,
Status indication LED	yellow
Device protection Electrical	
Rated insulation voltage	3750 V
Device protection Media	
Flame resistance	flame retardant
Mechanical data Material data	
Color housing	black
Material housing	Plastic
Mechanical data Mounting data	
Mounting method	geschnappt
Suitable for mounting type	mounting rail, (EN 60715)
Height	91 mm
Width	6,2 mm
Depth	70 mm
Environmental characteristics Climatic	
Operating temperature min.	-20 °C
Operating temperature max.	60 °C
Storage temperature min.	-40 °C
Storage temperature max.	80 °C
Connection type 5	
Connection	Screw terminals SK
Family construction form	terminal
Gender	female
Color contact carrier	black
No. of poles	1
PIN 1	-
Connection	Screw terminals SK
Family construction form	terminal
•	

The information in this Product-PDF has been compiled with the utmost care. Liability for the correctness completeness and topicality of the information is restricted to gross negligence. Version: 2024-05-20



Gender	female
Color contact carrier	black
No. of poles	1
PIN 1	+
Connection	Screw terminals SK
Family construction form	terminal
Gender	female
Color contact carrier	black
No. of poles	1
PIN 1	In
Connection	Screw terminals SK
Family construction form	terminal
Gender	female
Color contact carrier	black
No. of poles	1
PIN 1	14
Connection	Screw terminals SK
Family construction form	terminal
Gender	female
Color contact carrier	black
No. of poles	1
PIN 1	13