

VALVE PLUG SUPPRESSOR FORM A - 18MM

RC and LED, 230VAC/DC/10VA/W


230 V AC/DC RC + LED


Remove plug gasket when fitting adapter. Other LED colors on request.

Link to Product

Illustration







Product may differ from Image







| 27371013 | |
|----------|--|
| 27371013 | |
| 27371013 | |
| 27371013 | |
| 27371013 | |
| 27371013 | |
| | 27371013 27371013 27371013 27371013 |



stay connected

| ECLASS-11.1 | 27371013 |
|--|-----------------|
| ECLASS-12.0 | 27371013 |
| ETIM-5.0 | EC000197 |
| customs tariff number | 85363010 |
| GTIN | 4048879012188 |
| Packaging unit | 1 |
| Electrical data | |
| Capacity CX | 20 ms |
| Holding power max. | 10 W |
| Electrical data Supply | |
| Cut-off peak voltage max. | 300 V |
| Electrical data Input | |
| Input voltage AC min. | 110 V |
| Input voltage AC max. | 250 V |
| Input voltage DC min. | 110 V |
| Input voltage DC max. | 250 V |
| Diagnostics | |
| Status indication LED | yellow |
| Device protection Media | |
| Flame resistance | flame retardant |
| Mechanical data Material data | |
| Coating contact | silver-plated |
| Color housing | black |
| Material housing | PA |
| Material contact | Bronze |
| Mechanical data Mounting data | |
| Height | 37 mm |
| Width | 45 mm |
| Depth | 30 mm |
| Environmental characteristics Climatic | |
| Operating temperature min. | -20 °C |
| Operating temperature max. | 60 °C |
| Housing temperature max. (EN 61347-2-13) | 130 °C |