

## **VALVE PLUG SUPPRESSOR FORM A - 18MM**

RC and LED, 24VAC/DC/10VA/W


24 V AC/DC RC + LED


Remove plug gasket when fitting adapter. Other LED colors on request.

## **Link to Product**

## Illustration







Product may differ from Image







Commercial data		
ECLASS-6.0	27371013	
ECLASS-6.1	27371013	
ECLASS-7.0	27371013	
ECLASS-8.0	27371013	
ECLASS-9.0	27371013	
ECLASS-10.1	27371013	



ECLASS-11.1	27371013
ECLASS-12.0	27371013
ETIM-5.0	EC000197
customs tariff number	85363010
GTIN	4048879012157
Packaging unit	1
Electrical data	
Capacity CX	20 ms
Holding power max.	10 W
Electrical data   Supply	
Cut-off peak voltage max.	105 V
Electrical data   Input	
Input voltage AC min.	12 V
Input voltage AC max.	30 V
Input voltage DC min.	12 V
Input voltage DC max.	30 V
Diagnostics	
Status indication LED	yellow
Device protection   Media	
Flame resistance	flame retardant
Mechanical data   Material data	
Coating contact	silver-plated
Color housing	black
Material housing	PA
Material contact	Bronze
Mechanical data   Mounting data	
Height	37 mm
Width	45 mm
Depth	30 mm
Environmental characteristics   Climatic	
Operating temperature min.	-20 °C
Operating temperature max.	60 °C
Housing temperature max. (EN 61347-2-13)	130 °C