

## **VALVE PLUG SUPPRESSOR FORM CI - 9.4MM**

Zener diode and LED, 24VAC/DC/100VA/W


24 V AC/DC Z-Diode + LED


Remove plug gasket when fitting adapter. Other LED colors on request.

## **Link to Product**

## Illustration







Product may differ from Image







Commercial data		
ECLASS-6.0	27371013	
ECLASS-6.1	27371013	
ECLASS-7.0	27371013	
ECLASS-8.0	27371013	
ECLASS-9.0	27371013	
ECLASS-10.1	27371013	



stay connected

ECLASS-11.1	27371013
ECLASS-12.0	27371013
ETIM-5.0	EC000197
customs tariff number	85363010
GTIN	4048879011587
Packaging unit	1
Electrical data	
Capacity CX	20 ms
Holding power max.	100 W
Electrical data   Supply	
Cut-off peak voltage max.	55 V
Electrical data   Input	
Input voltage AC min.	18 V
Input voltage AC max.	30 V
Input voltage DC min.	18 V
Input voltage DC max.	30 V
Diagnostics	
Status indication LED	yellow
Device protection   Media	
Flame resistance	flame retardant
Mechanical data   Material data	
Coating contact	silver-plated
Color housing	black
Material housing	PA
Material contact	Bronze
Mechanical data   Mounting data	
Height	27 mm
Width	27,5 mm
Depth	15,5 mm
Environmental characteristics   Climatic	
Operating temperature min.	-20 °C
Operating temperature max.	60 °C
Housing temperature max. (EN 61347-2-13)	130 °C