

MIRO TR 24VDC FK 4P OPTO-COUPLER MODULE


IN: 53 VDC - OUT: 48 VDC / 0,5 A


Transistor 0.5 A 24 V DC Spring clamp terminals

Link to Product

Illustration







Product may differ from Image









27371601		
27371604		
27371604		
27371604		
27371604		
27371604		
	27371604 27371604 27371604 27371604	27371604 27371604 27371604 27371604



stay connected

ECLASS-11.1	27371604
ECLASS-12.0	27371604
ETIM-5.0	EC001504
customs tariff number	85414900
GTIN	4048879021883
Packaging unit	1
Electrical data Input	
	• •
Input voltage OFF DC min.	0 V
Input voltage OFF DC max.	5 V
Input voltage DC min.	10 V
Input voltage DC max.	53 V
Current input DC	14 mA
Electrical data Output	
Switch off delay max.	400 μs
Quiescent current OFF max.	0,01 mA
Switching frequency inductive max.	100 Hz
Switching frequency ohmic max.	1000 Hz
Voltage switching DC min.	5 V
Switching voltage DC max.	48 V
Switching current min.	0,1 mA
Switching current max.	0,5 A
Voltage drop DC max.	1,2 V
Diagnostics	
Status indication LED	yellow
Device protection Electrical	
Rated insulation voltage	3750 V
Device protection Media	
Flame resistance	flame retardant
Mechanical data Material data	
Color housing	black
Material housing	Plastic
Mechanical data Mounting data	
Mounting method	geschnappt
Suitable for mounting type	mounting rail, (EN 60715)
Height	78 mm
Width	6,2 mm
Depth Formantal sharestaviation Climat	70 mm
Environmental characteristics Climat	
Operating temperature min. Operating temperature max.	-20 °C 60 °C
	00 0
Connection type 4	Spring alamn terminals EV
Connection Form	Spring clamp terminals FK
Family construction form	terminal
Gender Color contact corrier	female
Color contact carrier	black
No. of poles	1
PIN 1	13 +
Connection	Spring clamp terminals FK
Family construction form	terminal
Gender	female

The information in this Product-PDF has been compiled with the utmost care. Liability for the correctness completeness and topicality of the information is restricted to gross negligence. Version: 2024-05-20



Color contact carrier	black
No. of poles	1
PIN 1	14
Connection	Spring clamp terminals FK
Family construction form	terminal
Gender	female
Color contact carrier	black
No. of poles	1
PIN 1	A 1
Connection	Spring clamp terminals FK
Family construction form	terminal
Gender	female
Color contact carrier	black
No. of poles	1
PIN 1	A 2