



MIRO 6.2 PLUGGABLE COMPL.MODULE OUTPUT RELAY

IN: 12 VAC/DC - OUT: 250 VAC/30VDC / 6 A

- 1 NO/NC contact
- 6 A
- 12 V AC/DC
- Spring clamp terminals

[Link to Product](#)

Illustration



Product may differ from Image



| Commercial data |          |
|-----------------|----------|
| ECLASS-6.0      | 27371601 |
| ECLASS-6.1      | 27371601 |
| ECLASS-7.0      | 27371601 |
| ECLASS-8.0      | 27371601 |
| ECLASS-9.0      | 27371601 |
| ECLASS-10.1     | 27371601 |

|                       |               |
|-----------------------|---------------|
| ECLASS-11.1           | 27371601      |
| ECLASS-12.0           | 27371601      |
| ETIM-5.0              | EC001437      |
| customs tariff number | 85364900      |
| GTIN                  | 4048879021340 |
| Packaging unit        | 1             |

**Electrical data | Input**

|                       |         |
|-----------------------|---------|
| Input voltage AC min. | 9,8 V   |
| Input voltage AC max. | 14 V    |
| Input voltage DC min. | 9,8 V   |
| Input voltage DC max. | 14 V    |
| Input current         | 14,2 mA |

**Electrical data | Output**

|                                               |                                          |
|-----------------------------------------------|------------------------------------------|
| Utilization category AC-12 (EN IEC 60947-5-1) | 6 A @ 24, 6 A @ 110 V, 6 A @ 230 V       |
| Utilization category AC-15 (EN IEC 60947-5-1) | 3 A @ 24 V, 3 A @ 110 V, 1,5 A @ 230 V   |
| Utilization category DC-13 (EN IEC 60947-5-1) | 1 A @ 24 V, 0,2 A @ 110 V, 0,1 A @ 230 V |
| Switching frequency max.                      | 10 Hz                                    |
| Power rating AC max.                          | 1500 VA                                  |
| Power rating DC max.                          | 180 W                                    |
| Switching voltage AC max.                     | 250 V                                    |
| Switching voltage DC max.                     | 30 V                                     |
| Switching current DC                          | 100 mA                                   |
| Switching current max.                        | 6 A                                      |

**Diagnostics**

|                       |       |
|-----------------------|-------|
| Status indication LED | green |
|-----------------------|-------|

**Device protection**

|                    |                |
|--------------------|----------------|
| Condition lifetime | load-dependent |
|--------------------|----------------|

**Device protection | Electrical**

|                                     |              |
|-------------------------------------|--------------|
| Degree of protection (EN IEC 60529) | IP20         |
| Rated insulation voltage            | 250 V        |
| Electrical lifetime NC              | 10000 Cycles |
| Electrical lifetime NO              | 30000 Cycles |

**Device protection | Mechanical**

|                      |                 |
|----------------------|-----------------|
| Mechanical endurance | 10000000 Cycles |
|----------------------|-----------------|

**Mechanical data**

|                    |      |
|--------------------|------|
| Drop-out time max. | 4 ms |
| Response time max. | 8 ms |

**Mechanical data | Material data**

|                  |          |
|------------------|----------|
| Material contact | Ag Sn O2 |
|------------------|----------|

**Mechanical data | Mounting data**

|                            |                           |
|----------------------------|---------------------------|
| Mounting method            | geschnappt                |
| Suitable for mounting type | mounting rail, (EN 60715) |
| Height                     | 93 mm                     |
| Width                      | 6,2 mm                    |
| Depth                      | 75,6 mm                   |

**Environmental characteristics | Climatic**

|                            |        |
|----------------------------|--------|
| Operating temperature min. | -25 °C |
| Operating temperature max. | 60 °C  |