

## SIGNAL TOWER MODLIGHT30 EQUIPPED WITH LED MODULES

Green, amber, red with 4 pole M12 connection

Connection module + LED modules green, yellow, red with M12 connection Connection cables are in the online shop under "Connection Technology".

## **Link to Product**

## Illustration



Product may differ from Image





Commercial data	
ECLASS-6.0	27371230
ECLASS-6.1	27371230
ECLASS-7.0	27371230
ECLASS-8.0	27371230
ECLASS-9.0	27371230
ECLASS-10.1	27371230
ECLASS-11.1	27371230
ECLASS-12.0	27371230
ETIM-5.0	EC001042
customs tariff number	85318070
GTIN	4048879496896
Packaging unit	1
Electrical data   Supply	
Operating voltage AC	24 V
Operating voltage DC	24 V
Current consumption max.	85 mA
Device protection   Electrical	
Degree of protection (EN IEC 60529)	IP65
Mechanical data   Material data	
Color housing	black

The information in this Product-PDF has been compiled with the utmost care.

Liability for the correctness completeness and topicality of the information is restricted to gross negligence. Version: 2024-05-17



Material housing	Plastic
Mechanical data   Mounting data	
Height	30 mm
Width	30 mm
Depth	213 mm
Environmental characteristics   Climatic	
Operating temperature min.	-20 °C
Operating temperature max.	60 °C
Connection type 1	
Family construction form	M12
Gender	male
Coding	A
No. of poles	4
PIN 1	GN
PIN 2	RD
PIN 3	COM
PIN 4	YE