

## B10 Bulkhead mounted h., IP65

Single locking lever m., p-cover


B10 Bulkhead mounted housing Single locking lever IP65

Technical data will be only guaranteed with Murrelektronik components.

## **Link to Product**

## Illustration





Product may differ from Image

Commercial data	
ECLASS-6.0	27143424
ECLASS-6.1	27261203
ECLASS-7.0	27440202
ECLASS-8.0	27440202
ECLASS-9.0	27440202
ECLASS-10.1	27440202
ECLASS-11.1	27440202
ECLASS-12.0	27440202
ETIM-5.0	EC000437
customs tariff number	85389099
GTIN	4048879644969
Packaging unit	1
Installation   Connection	
Mating cycles min.	500
Device protection   Electrical	
Degree of protection (EN IEC 60529)	IP65
Additional condition protection degree	inserted, locked, with screw connection
Mechanical data	
Housing type	Bulkhead mounted housing
Mechanical data   Material data	
Coating housing	powder-coated
Coating locking	verzinkt
Material gasket	NBR

The information in this Product-PDF has been compiled with the utmost care. Liability for the correctness completeness and topicality of the information is restricted to gross negligence. Version: 2024-05-18



Material housing	Aluminum die casting
Material protective cover	Plastic
Locking material	Steel
Mechanical data   Mounting data	
Size	B10
Height	28,5 mm
Width	43 mm
Depth	93 mm
Looking techniques	Single locking lever
Environmental characteristics   Climat	tic
Operating temperature min.	-40 °C
Operating temperature max.	100 °C
Climatic category (EN IEC 60068-1)	40/100/21